



VERIFICATION

The undersigned, of the below address, hereby certifies that he/she well knows both the English and Japanese languages, and that the attached is an accurate English translation of the Japanese Patent application filed on September 30, 2002 under No. P2002-287267.

The undersigned declares further that all statements made herein of his/her own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Signed this 3rd day of December, 2007.

Signature:

Name: Shiro TERASAKI

Address: c/o Soei Patent & Law Firm Ginza First Bldg.,
10-6, Ginza 1-chome, Chuo-ku, Tokyo 104-0061
Japan



JAPAN PATENT OFFICE

This is to certify that the annexed is a true copy of the following application as filed with this Office.

Date of Application: September 30, 2002

Application Number: Japanese Patent Application
No. 2002-287267

Applicant(s): HAMAMATSU PHOTONICS K.K.

Commissioner,

Patent Office

(Seal)

(Document Name) Patent Application
(Reference Number) 2002-0538
(Particular Note) Patent application applied for under the
provision set forth in Article 30, Paragraph
1 of the Patent Law
(Presentation Date) September 30, 2002
(Directly) Commissioner of the Patent Office
(IPC) B41J 2/205
B41J 2/21
B41J 2/175

(Inventor)

(Residence or Address)

c/o Hamamatsu Photonics K.K.,
1126-1, Ichino-cho, Higashi-ku, Hamamatsu-shi, Shizuoka

(Name) Osamu YOGI

(Inventor)

(Residence or Address)

c/o Hamamatsu Photonics K.K.,
1126-1, Ichino-cho, Higashi-ku, Hamamatsu-shi, Shizuoka

(Name) Tomonori KAWAKAMI

(Applicant)

(Identification Number) 000236436

(Name) HAMAMATSU PHOTONICS K.K.,

(Attorney)

(Identification Number) 100088155

(Patent Attorney)

(Name) Yoshiki HASEGAWA
(Attorney)
(Identification Number) 100089978
(Patent Attorney)
(Name) Tatsuya SHIODA
(Attorney)
(Identification Number) 100092657
(Patent Attorney)
(Name) Shiro TERASAKI
(Attorney)
(Identification Number) 100107191
(Patent Attorney)
(Name) Noriaki NAGAHAMA
(Official Fee)
(Pre-Paid Master Note Number) 014708
(Amount to be paid) 21,000
(Lists of the Article to be presented)
(Name of Article) Specification 1
(Name of Article) Drawing 1
(Name of Article) Abstract 1
(Proof Reading) Required

[Document Name] Specification

[Title of the Invention]

Mixed Liquid Droplet Forming Method and Apparatus, Ink Jet Printing
Method and Apparatus, and Ink Jet Printing Electrode-Attached Nozzle

5 [Claims]

[Claim 1] A mixed liquid droplet forming method comprising: a first step
in which a voltage is applied first between a raw material liquid housed
in one of a plurality of nozzles and a flat electrode disposed opposite the
nozzle to discharge the raw material liquid from the front end of the
10 nozzle and form a droplet made of the raw material liquid on a droplet
forming object disposed between the front end of the nozzle and the flat
electrode; and

a second step in which a voltage is applied between a raw
material liquid housed in the other nozzle of the plurality of nozzles and
15 the flat electrode to discharge the raw material liquid from the front end
of the nozzle, and the droplet is mixed with the raw material liquid to
form a droplet of the mixed liquid.

[Claim 2] The mixed liquid droplet forming method according to Claim
1,

20 wherein in the first step, an electrode is provided on the outer
circumference of at least one nozzle of the plurality of nozzles and the
electrode is supplied with a potential equal to or higher than the
potential of a raw material liquid inside the nozzle.

[Claim 3] A mixed liquid droplet forming apparatus, comprising:

a plurality of nozzles that house a plurality of raw material liquids and discharge the plurality of raw material liquids independently from each other;

5 a flat electrode disposed opposite the front ends of the plurality of nozzles; and

a voltage applying unit that applies a voltage between raw material liquids housed in the plurality of nozzles and the flat electrode.

10 [Claim 4] The mixed liquid droplet forming apparatus according to Claim 3, further comprising a control unit that controls the voltage applying apparatus so that a voltage is applied to an arbitrary raw material liquid among the plurality of raw material liquids.

[Claim 5] The mixed liquid droplet forming apparatus according to Claim 4,

15 wherein an electrode is provided on the outer circumference of at least one nozzle of the plurality of nozzles, and the control unit controls the voltage applying unit so that the electrode is supplied with a potential equal to or higher than the potential of the raw material liquid.

[Claim 6] An ink jet printing method for printing a color image on a printing object by using a plurality of inks, comprising:

20 a first step in which a plurality of ink nozzles which house the plurality of inks and a dilution nozzle which houses a dilute solution that can dilute the inks are used, and the ink or the dilute solution is discharged from the ink nozzle or the dilution nozzle by an electrostatic sucking force to form a droplet on the printing object; and

a second step in which the ink or the dilute solution is discharged from the ink nozzle or the dilution nozzle by an electrostatic sucking force, and the inks or the dilute solution are mixed in the droplet to form a droplet in an additive color.

5 [Claim 7] The ink jet printing method according to Claim 6,

wherein in the first step, a droplet made of the dilute solution is formed on a printing object by discharging the dilute solution from the dilution nozzle.

10 [Claim 8] The ink jet printing method according to Claim 6, further comprising, after the second step, a step in which the chroma of the droplet is measured, and based on the measured chroma, the quantity of discharging the ink or the dilute solution is controlled so that the chroma of the droplet becomes a desired chroma.

[Claim 9] The ink jet printing method according to Claim 7 or 8,

15 wherein in the first step, an electrode is provided on the outer circumference of the dilution nozzle and the electrode is supplied with a potential equal to or higher than the potential of the dilute solution inside the dilution nozzle.

20 [Claim 10] An ink jet printing apparatus for printing a color image on a printing object by using a plurality of inks, comprising:

a plurality of ink nozzles which house the plurality of inks, respectively

a dilution nozzle which houses a dilute solution that can dilute the inks;

a flat electrode disposed opposite the front ends of the ink nozzles and the dilution nozzle; and

a voltage applying unit which applies a voltage between the inks and the dilute solution and the flat electrode, wherein

5 the plurality of ink nozzles and the dilution nozzle are disposed apart from each other.

[Claim 11] The ink jet printing apparatus according to Claim 10, further comprising a control unit which controls the voltage applying unit so that a voltage is applied to an arbitrary liquid among the inks and the dilute solution.

10

[Claim 12] The ink jet printing apparatus according to Claim 11,

wherein an electrode is provided on the outer circumference of the dilution nozzle, and the control unit controls the voltage applying unit so that the electrode is supplied with a potential equal to or higher than the potential of the dilute solution.

15

[Claim 13] The ink jet printing apparatus according to Claim 11, further comprising:

an illuminating light source which illuminates a droplet formed on the printing object; and

20

a chroma measuring unit which measures the chroma of the droplet illuminated by the illuminating light source, wherein

the control unit controls the voltage applying unit based on the chroma of the droplet measured by the chroma measuring unit so that the chroma of the droplet becomes a desired chroma and adjusts the

quantity of discharging the ink or the dilute solution.

[Claim 14] An ink jet printing electrode-attached nozzle which is used in an ink jet printing apparatus including a flat electrode and disposed opposite the flat electrode, comprising a nozzle that houses ink or a dilute solution and an electrode that is provided on the outer circumference of the nozzle.

[Detailed Description of the Invention]

[0001]

[Technical Field to which the Invention Pertains]

The present invention relates to mixture droplet forming method and apparatus, ink jet printing method and apparatus, and an ink jet printing electrode-attached nozzle.

[0002]

[Prior Art]

Generally, an ink jet printing apparatus forms color images by stamping three primary color inks (C (cyan), M (magenta), and Y (yellow)) corresponding to three primary colors or four primary color inks (including K (black) in addition to the C, M, and Y) onto a printing object, and expresses additive colors by changes in dot density.

[0003] However, in expression of additive colors by changes in dot density, a subtle color cannot be satisfactorily expressed or a resultant provides a sense of roughness.

[0004] As an inkjet printing apparatus solving this problem, for example, one is disclosed in Japanese Published Unexamined Patent Application

No. H08-207318 as described below. FIG. 7 is a schematic sectional view showing the ink jet printing apparatus described in the same publication. This ink jet printing apparatus 100 applies a voltage between a ring-shaped electrode 101 and an electrode plate 102 by a power supply 108, discharges a concentrated ink 104 from a liquid feed pipe 103, and forms a droplet made of the ink on a printing object 105 on the electrode plate 102. When adjusting the ink density, the concentrated ink 104 is sucked out of the liquid feed pipe 103, and simultaneously, a transparent solvent 107 is sucked out of the liquid feed pipe 106 and the concentrated ink is diluted by the transparent solvent, and the diluted droplet is discharged to form a droplet the ink density of which has been adjusted on the printing object 105.

[0005] [Patent Document 1] Japanese Published Unexamined Patent Application No. H08-207318

[0006]

[Problem to be Solved by the Invention]

However, the ink jet printing apparatus 100 described in the above-mentioned conventional published application has the following problem.

[0007] That is, in the ink jet printing apparatus 100, a liquid that is cut off and left on the liquid feed pipe 103 side after being discharged is a mixed liquid of the concentrated ink and the transparent solvent, and the mixed liquid remains inside the liquid feed pipe 103. Therefore, when this remaining liquid and other color ink are mixed thereafter, an

unintended color is printed on the printing object. Therefore, in the method for adjusting the ink density as described above, it is difficult to realize an accurate subtle color.

[0008] Therefore, an object of the invention is to provide a mixed liquid droplet forming method and apparatus, an ink jet printing method and apparatus, and an ink jet printing electrode-attached nozzle, by which liquids to be discharged independently from each nozzle can be accurately mixed on a droplet forming object.

[0009]

[Means for Solving the Problem]

In order to solve the above-mentioned problem, the invention provides a mixed liquid droplet forming method comprising a first step in which a voltage is applied first between a raw material liquid housed in one of a plurality of nozzles and a flat electrode disposed opposite the nozzle to discharge the raw material liquid from the front end of the nozzle and form a droplet made of the raw material liquid on a droplet forming object disposed between the front end of the nozzle and the flat electrode, and a second step in which a voltage is applied between a raw material liquid housed in the other nozzle of the plurality of nozzles and the flat electrode to discharge the raw material liquid from the front end of the nozzle, and the droplet is mixed with the raw material liquid to form a droplet of the mixed liquid.

[0010] According to this invention, a voltage is applied first between a raw material liquid housed in one of the plurality of nozzles and the flat

electrode and the raw material liquid is discharged from the front end of the nozzle to form a droplet made of the raw material liquid on a droplet forming object. At this point, due to the existence of the droplet, the equipotential line becomes convex toward the nozzle side. Therefore, when a voltage is applied between a raw material liquid housed in the other nozzle and the flat electrode, the electrical field becomes greater along the line connecting the raw material liquid and the droplet. Therefore, when the raw material liquid housed in the other nozzle is discharged, the raw material liquid is guided to this droplet, and the raw material liquids are accurately mixed within the droplet.

[0011] Preferably, in the first step, an electrode is provided on the outer circumference of at least one nozzle of the plurality of nozzles and the electrode is supplied with a potential equal to or higher than the potential of a raw material liquid inside the nozzle.

[0012] In this case, the electrical line of force concentrates immediately under the nozzle provided with the electrode, so that it becomes possible to accurately dispose the raw material liquid at a desired position on the droplet forming object. Therefore, when the raw material liquid is discharged toward the droplet forming object, the raw material liquid can be accurately mixed with the droplet on the droplet forming object. Furthermore, raw material liquids are not mixed before they are discharged but are mixed after they are discharged. Accordingly, the qualities of the raw material liquids do not change inside the nozzles. Therefore, even when a droplet is repeatedly formed on the droplet

forming object, a droplet with an intended quality can be formed as one dot.

[0013] In addition, the invention provides a mixed liquid droplet forming apparatus, comprising a plurality of nozzles that house a plurality of raw material liquids and discharge the plurality of raw material liquids independently from each other, a flat electrode disposed opposite the front ends of the plurality of nozzles, and a voltage applying unit that applies a voltage between raw material liquids housed in the plurality of nozzles and the flat electrode.

[0014] According to this droplet forming apparatus, when a voltage is applied between a raw material liquid housed in one of the plurality of nozzles and the flat electrode by the voltage applying unit, the raw material liquid is discharged from the nozzle to form a droplet on the droplet forming object. At this point, due to the existence of the droplet, the equipotential line becomes convex toward the nozzle side. Therefore, when a voltage is applied between a raw material liquid housed in the other nozzle and the flat electrode, the electrical field becomes greater along the line connecting this raw material liquid and the droplet. Therefore, when the raw material liquid housed in the other nozzle is discharged, this raw material liquid is guided to this droplet and the raw material liquids are accurately mixed within this droplet.

[0015] The mixed liquid droplet forming apparatus may further comprise a control unit that controls the voltage applying apparatus so that a voltage is applied to an arbitrary raw material liquid among the

plurality of raw material liquids.

[0016] Preferably, in the mixed liquid droplet forming apparatus, an electrode is provided on the outer circumference of at least one nozzle of the plurality of nozzles, and the control unit controls the voltage
5 applying unit so that the electrode is supplied with a potential equal to or higher than the potential of the raw material liquid.

[0017] In this case, when the voltage applying unit is controlled by the control unit so as to supply a potential higher than the potential of the raw material liquid to the electrode, the electrical line of force further
10 concentrates immediately under the nozzle. Therefore, it becomes possible to dispose the raw material liquid at a desired position on the droplet forming object. Therefore, after that, when the raw material liquid is discharged toward the droplet forming object, it can be accurately mixed with the droplet made of a raw material liquid.
15 Furthermore, the raw material liquids are not mixed before they are discharged from the nozzles but are mixed on the droplet forming object after they are discharged, so that the qualities of the raw material liquids are not changed inside the nozzles. Therefore, a droplet with an intended quality can be formed as one dot.

[0018] According to an ink jet printing method relating to the invention, the ink jet printing method for printing a color image on a printing
20 object by using a plurality of inks, comprises a first step in which a plurality of ink nozzles which house the plurality of inks and a dilution nozzle which houses a dilute solution that can dilute the inks are used,

and the ink or the dilute solution is discharged from the ink nozzles or the dilution nozzle by an electrostatic sucking force to form a droplet on the printing object, and a second step in which the ink or the dilute solution is discharged from the ink nozzle or the dilution nozzle by an electrostatic sucking force, and the inks or the dilute solution are mixed in the droplet to form a droplet in an additive color.

[0019] According to this invention, first, a voltage is applied between the ink or the dilute solution housed in one of the ink nozzles and the dilution nozzle and the flat electrode, and the ink or dilute solution is discharged from the front end of the ink nozzle or dilution nozzle to form a droplet made of the primary color ink or dilute solution on a printing object. At this point, due to the existence of the droplet, the equipotential line becomes convex toward the nozzle side. Therefore, next, when a voltage is applied between the ink or dilute solution housed in the other nozzle and the flat electrode, the electrical field becomes great along the line connecting this ink or dilute solution and the droplet. Therefore, when the ink or dilute solution housed in the other nozzle is discharged, this liquid is guided to this droplet, and the inks or the ink and the dilute solution are accurately mixed within this droplet, whereby a droplet in an additive color is formed.

[0020] Preferably, in the first step, a droplet made of the dilute solution is formed on a printing object by discharging the dilute solution from the dilution nozzle.

[0021] In this case, when the ink is mixed with the droplet after the

second step, color change of the droplet due to proceeding with the color mixture can be easily judged.

[0022] Preferably, after the second step, the method further comprises a step in which the chroma of the droplet is measured, and based on the measured chroma, the quantity of discharging the inks or the dilute solution is controlled so that the chroma of the droplet becomes a desired chroma.

[0023] In this case, a target additive color can be accurately expressed.

[0024] Preferably, in the ink jet printing method, an electrode is provided on the outer circumference of the dilution nozzle and the electrode is supplied with a potential equal to or higher than the potential of the dilute solution inside the dilution nozzle.

[0025] In this case, since the electrical line of force concentrates immediately under the dilution nozzle, the dilute solution can be accurately disposed at a desired position on a printing object. Therefore, after that, when the ink is discharged to the printing object, it can be accurately mixed with the droplet made of the dilute solution. Furthermore, the dilute solution and the ink are not mixed before they are discharged but are mixed on the printing object after they are discharged. Therefore, inks do not change in quality in the respective ink nozzles. Therefore, even when a droplet is repeatedly formed, a droplet in an intended additive color can be formed as one dot, and printing with high accuracy without distortion is realized.

[0026] According to the ink jet printing apparatus of the invention, the

ink jet printing apparatus for printing a color image on a printing object by using a plurality of inks, comprises a dilution nozzle which houses a dilute solution that can dilute the inks, a flat electrode disposed opposite the front ends of the ink nozzles and the dilution nozzle, and a voltage
5 applying unit which applies a voltage between the inks and the dilute solution and the flat electrode, wherein the plurality of ink nozzles and the dilution nozzle are disposed apart from each other.

[0027] According to this ink jet printing apparatus, when a voltage is applied between the ink or dilute solution and the flat electrode by the
10 voltage applying unit, the ink or dilute solution is discharged from the ink nozzle or dilution nozzle to form a droplet on a printing object. At this point, due to the existence of the droplet, the equipotential line becomes convex toward the nozzle side. Therefore, when a voltage is applied between the ink or dilute solution housed in the other nozzle
15 and the flat electrode, the electrical field becomes greater along the line connecting the ink or dilute solution and the droplet. Therefore, when the ink or dilute solution housed in the other nozzle is discharged, this liquid is guided to this droplet, and the inks or the ink and the dilute solution are accurately mixed within this droplet, whereby a droplet in
20 an additive color is formed.

[0028] The ink jet printing apparatus may further comprise a control unit which controls the voltage applying unit so that a voltage is applied to an arbitrary liquid among the inks and the dilute solution.

[0029] Preferably, in the ink jet printing apparatus, an electrode is

provided on the outer circumference of the dilution nozzle, and the control unit controls the voltage applying unit so that the electrode is supplied with a potential equal to or higher than the potential of the dilute solution.

5 [0030] In this case, when the voltage applying unit is controlled by the control unit so as to supply a potential equal to or higher than the potential of the dilute solution to the electrode, the electrical line of force further concentrates immediately under the dilution nozzle. Therefore, it becomes possible to dispose the dilute solution at a desired
10 position on the printing object. Therefore, after that, when the ink is discharged toward the printing object, it can be accurately mixed with the droplet made of the dilute solution. Furthermore, the dilute solution and the ink are not mixed before they are discharged from the nozzles but are mixed on the printing object after they are discharged, so that
15 the ink densities do not change in the ink nozzles. Therefore, a droplet in an intended additive color can be formed as one dot, whereby printing with high accuracy without distortion is realized.

[0031] Preferably, the ink jet printing apparatus further comprises an illuminating light source which illuminates a droplet formed on the
20 printing object, and a chroma measuring unit which measures the chroma of the droplet illuminated by the illuminating light source, wherein the control unit controls the voltage applying unit based on the chroma of the droplet measured by the chroma measuring unit so that the chroma of the droplet becomes a desired chroma and adjusts the

quantity of discharging the ink or the dilute solution.

[0032] In this case, a target additive color can be accurately expressed.

[0033] Furthermore, according to the invention, an ink jet printing electrode-attached nozzle which is used in an ink jet printing apparatus including a flat electrode and disposed opposite the flat electrode, comprises a nozzle housing an ink or dilute solution and an electrode provided on the outer circumference of the nozzle.

[0034] According to this ink jet printing electrode-attached nozzle, when it is used in an ink jet printing apparatus including a flat electrode, a printing object is disposed between the nozzle and the flat electrode, a voltage is applied between an ink or dilute solution housed in the nozzle and the flat electrode, and furthermore, the electrode is supplied with a potential equal to or higher than that of the ink or the dilute solution, whereby the electrical line of force further concentrates immediately under the electrode-attached nozzle, and therefore, the ink or dilute solution can be accurately disposed at a desired position on the printing object. Therefore, after that, when the ink or dilute solution is discharged to the printing object, it can be accurately mixed with the droplet on the printing object.

[0035]

[Embodiments of the Invention]

Hereinafter, embodiments of the invention are described in detail.

[0036] FIG. 1 is a schematic view showing a main part of an embodiment of the ink jet printing apparatus of the invention, and FIG.

2 is a bottom view of a nozzle head. As shown in FIG. 1, the ink jet printing apparatus 1 of this embodiment has a nozzle head 2, and a flat electrode 3 is disposed opposite the nozzle head 2. On the flat electrode 3, a recording sheet (droplet forming object) 4 as a printing object is placed. The nozzle head 2 can be made to reciprocate in the arrow A direction of FIG. 1 by a nozzle head transport system 5, and the recording sheet 4 can be moved in the arrow B direction orthogonal to the arrow A direction by a chart drive mechanism 6.

[0037] As shown in FIG. 2, the nozzle head 2 has a nozzle holder 7, and in the nozzle holder 7, a dilution nozzle 8 housing dilution liquid (raw material liquid) and four ink nozzles 9a to 9d housing four primary color inks (raw material liquids) corresponding to four primary colors are inserted and fixed. A dilution nozzle 8 and the ink nozzles 9a through 9d are made of glass in terms of dimensional stability. The four primary color inks are C (cyan), M (magenta), Y (yellow), and K (black), and the ink nozzles 9a through 9d house the C ink, M ink, Y ink, and K ink, respectively. The dilution nozzle 8 is connected to a dilute solution supply tank (not shown), and the ink nozzles 9a through 9d are connected to ink supply tanks (not shown).

[0038] The ink nozzles 9a through 9d and the dilution nozzle 8 are disposed apart from each other. In detail, the dilution nozzle 8 is fixed to the center of the nozzle holder 7, and the ink nozzles 9a through 9d are disposed at equal intervals in a circle around the dilution nozzle 8. Disposition of the dilution nozzle 8 at the center is for discharging the

dilute solution first among the primary color inks and the dilution solution when forming one dot of droplet on the recording sheet 4. Therefore, when other primary color ink is discharged first when forming one dot of droplet on the recording sheet 4, this primary color ink is disposed at the center.

[0039] Furthermore, as shown in FIG. 1, the inks and the dilute solution housed in the ink nozzles 9a through 9d and the dilution nozzle 8 are electrically connected to the flat electrode 3 via a voltage applying unit 10 that can supply pulse voltages. Therefore, by the voltage applying unit 10, between the inks or the dilute solution and the flat electrode 3, voltages are applicable.

[0040] In the nozzle holder 7, an illuminating fiber 11 and a light receiving fiber 12 are inserted and fixed at positions axisymmetrical to each other about the dilution nozzle 8 (see FIG. 2). The illuminating fiber 11 is connected to a white light source (illuminating light source) 13, and the light receiving fiber 12 is connected to a chroma measuring unit 14 (see FIG. 1). Therefore, it becomes possible to illuminate a droplet by white light from the white light source 12 through the illuminating fiber 11, and light received from the droplet through the light receiving fiber 12 is received by the chroma measuring unit 14, and the chroma of the droplet is measured based on this light.

[0041] Furthermore, the ink jet printing apparatus 1 has a control unit 15, and by the control unit 15, the nozzle head transport system 5, the chart drive mechanism 6, the voltage applying unit 10, the white light

source 13, and the chroma measuring unit 14 can be controlled.

[0042] Next, an ink jet printing method using the above-described ink jet printing apparatus 1 is described with reference to FIG 3 and FIG 4.

[0043] FIG. 3 is a partial sectional view of the dilution nozzle, showing a condition where a dilute solution is discharged from the dilution nozzle and a droplet is formed on the recording sheet 4.

FIG 4(a) are timing charts of pulse voltages in

the nozzles, and FIG. 4 (b) to (f) are views showing a series of processes for forming a droplet in an additive color.

[0043] First, a pulse voltage is applied between the dilute solution and the flat electrode 3 by the voltage applying unit 10. At this point, as shown in the middle position of FIG. 4(a), a pulse voltage is formed by applying a voltage ΔE_2 between the timings t_1 and t_2 . Then, as shown in FIG. 3 and FIG. 4(b), the dilute solution 8a is sucked out of the dilution nozzle 8 by electrostatic sucking force to form a Taylor Cone 16, and then a predetermined quantity of the dilute solution is discharged and a droplet L made of the dilute solution is formed on the recording sheet 4.

[0044] Next, a voltage is applied between the Y ink stored in the ink nozzle 9c and the flat electrode 3 by the voltage applying unit. At this point, as shown in the upper position of FIG. 4(a), between the timings t_2 and t_3 , a pulse voltage is formed by applying the voltage ΔE_3 . At this point, due to the existence of the droplet formed on the recording sheet 4, the equipotential line is convex toward the nozzle 9c side, and the electrical field becomes greater along the line connecting the front end

of the ink nozzle 9c and the droplet.

Therefore, as shown in FIG 4(c), the Y ink is sucked out of the ink nozzle 9c by an electrostatic sucking force and forms a Taylor Cone, and then a predetermined quantity of the Y ink is discharged toward the droplet L. The Y ink causes turbulence when it enters in the droplet, whereby the Y ink and the dilute solution are mixed accurately.

[0045] At this point, as shown in FIG 4(d), the droplet L is illuminated by white light emitted from the white light source 13 through the illuminating fiber 11, and light emitted from the droplet L is received by the chroma measuring unit 14 through the light receiving fiber 12. Then, based on the chroma measured by the chroma measuring unit 14, an addition quantity of the Y ink or the dilute solution is adjusted so that the chroma of the droplet L becomes a desired chroma. In detail, this addition quantity is adjusted by the pulse period of the pulse voltage outputted from the voltage applying unit 10.

[0046] Next, a voltage is applied between the C ink housed in the ink nozzle 9a and the flat electrode 3 by the voltage applying unit 10. At this point, as shown in the lower position of FIG 4(a), between the timings t_3 and t_4 , a pulse voltage is formed by applying the voltage ΔE_1 . At this point, due to the existence of the droplet L formed on the recording sheet 4, the equipotential line is convex toward the ink nozzle 9a side, and therefore, the electrical field becomes greater along the line connecting the front end of the ink nozzle 9a and the droplet L. Therefore, as shown in FIG 4(e), the C ink is sucked out of the ink

nozzle 9a by an electrostatic sucking force and forms a Taylor Cone, and then a predetermined quantity of the C ink is discharged toward the droplet L. The C ink causes turbulence when it enters the inside of the droplet L, whereby the C ink and the dilute solution are accurately mixed.

[0047] At this point, as shown in FIG. 4(f), the droplet L is illuminated by white light emitted from the white light source 13 through the illuminating fiber 11, and light emitted from the droplet L is received by the chroma measuring unit 14 through the light receiving fiber 12. Then, in the same manner as described above, based on the chroma measured by the chroma measuring unit 14, the addition quantity of the C ink or the dilute solution is adjusted so that the chroma of the droplet L becomes a desired chroma.

[0048] Thereafter, the M ink and the K ink are injected into the droplet L as appropriate to form a droplet L in an additive color. The method for injecting the M ink and the K ink is the same as that for the Y ink. When forming a droplet L in an additive color, it is preferable that the color is gradually made darker from a light color, and a color with a target chroma is finally reached. Thereby, judgement on changes in color by chroma measurement can be made easily.

[0049] A droplet L in an additive color is thus formed on the recording sheet 4. This droplet L in the additive color is formed by mixture of primary color inks, however, mixture of primary color inks is not carried out before the inks are discharged from the nozzles, but is

carried out after they are discharged. Therefore, the densities of the primary color inks housed in the ink nozzles 9a through 9d are always maintained constant. Therefore, even when the ink jet printing apparatus 1 is repeatedly used, a droplet L formed on the recording sheet 4 can be accurately provided with an intended additive color.

After forming a droplet, the recording sheet 4 is moved in the arrow B direction of FIG. 1 by the chart transport system 6 or the nozzle head 2 is moved in the arrow A direction of FIG. 1 by the nozzle head transport system 5, a droplet is formed in the same manner as described above, and this operation is repeated, whereby a color image using real colors instead of false colors can be formed. The operations of the above-described nozzle head transport system 5, the chart transport system 6, the voltage applying unit 10, the white light source 13, and the chroma measuring unit 14 may be all controlled by the control unit 15.

[0050] Herein, for providing a droplet L with an intended additive color more accurately, it is preferable that the degree of color mixture of the droplet L is judged every time each ink is injected into the droplet L.

[0051] In detail, the following operation is carried out for judging the degree of color mixture of the droplet L.

Namely, the droplet L is illuminated by white light first, and the chroma of the droplet L is measured by using the chroma measuring unit 14. Next, the measured chroma is converted and a brightness index L^* according to the CIELAB color system and chroma coordinates a^* and

b* are calculated.

[0052] However, in this case, previous to color mixture, it is necessary that the mixture ratio of the primary color inks for realizing the target additive color and the values of L*, a* and b* of the primary color inks according to the ratio are prepared based on the data of the absorption spectra of the primary color inks.

[0053] Herein, an example of the process realizing the target additive color by judging the degree of color mixture of the droplet based on the measured chroma is described.

[0054] FIG. 5 is a flowchart for realizing the target additive color. As shown in FIG. 5, first, a droplet L made of a dilute solution is formed on the recording sheet 4 (Step 1).

[0055] Next, by setting the values of L*, a*, b* with respect to the target additive color as judgement criteria, it is judged whether the degree of mixture of the Y ink is high or low. If the degree is low, a unit quantity of the Y ink is added, and if the degree is high, a unit quantity of the dilute solution is added (Step 2). Herein, the unit quantity means the quantity of ink or dilute solution to be discharged when a voltage of one pulse is applied between the ink or dilute solution and the flat electrode 3.

[0056] Next, the values of L*, a*, and b* of the C-Y mixed ink with respect to the target additive color are set as judgement criteria, and it is judged whether the degree of mixture of the C ink is high or low. If it is low, a unit quantity of the C ink is added, and if it is high, a unit

quantity of the dilute solution is added (Step 3).

[0057] Next, the values of L^* , a^* and b^* of C-M-Y mixed ink with respect to the target additive color are set as judgement criteria, and it is judged whether the degree of mixture of the M ink is high or low. If it is low, a unit quantity of the M ink is added, and if it is high, a unit quantity of the dilute solution is added (Step 4).

[0058] Last, accurate values of L^* , a^* , and b^* with respect to the target additive color are set as judgement criteria, and it is judged whether the degree of mixture of the K ink is high or low. If it is low, a unit quantity of the K ink is added, and if it is high, a unit quantity of the dilute solution is added (Step 5).

[0059] Thus, the chroma of the droplet is measured every time an ink is injected into the droplet, and color mixture is carried out while the degrees of mixture of colors are judged, whereby the droplet L can be accurately provided with the target additive color.

[0060] Next, a second embodiment of the ink jet printing apparatus of the invention is described with reference to FIG. 6. In FIG. 6, components identical or equivalent to those of the first embodiment are attached with the same symbols and description thereof is omitted.

[0061] As shown in FIG. 6, the ink jet printing apparatus of this embodiment is different from the ink jet printing apparatus 1 of the first embodiment in that the dilution nozzle (electrode-attached nozzle) that has an electrode 20 on its outer circumference is provided.

[0062] Herein, the material forming the electrode 20 is not especially

limited as long as it has conductivity, however, such a material is preferably gold or platinum in terms of corrosion proof. The electrode 20 is formed by, for example, depositing the material on the front end of the dilution nozzle 8.

5 [0063] In the ink jet printing apparatus of this embodiment, to form the droplet L, the same voltage as the pulse voltage applied between, for example, the dilute solution 8a and the flat electrode 3 is applied between the electrode and the flat electrode 3.

10 [0064] Then, the electrostatic inductive charge 21 appearing at the front end of the electrode 20 biases the charge distribution of the electrostatic inductive charge 161 on the surface of the dilute solution so that the distribution becomes highest at the center of the nozzle, so that a great electrostatic force acts on the portion with the high charge density, that is, between the center of the dilute solution surface and the flat
15 electrode 3. As a result, the Taylor Cone 16 stays within the inner diameter portion of the nozzle end face, and the form thereof is deformed to be more acute. This is a result of concentration of the electrical line of force on the nozzle center portion. Therefore, the position where the droplet L is formed can be extremely stabilized. In
20 other words, the droplet L can be accurately formed at a desired position on the recording sheet 4.

[0065] After the droplet L is formed on the recording sheet 4, since primary color inks can be accurately injected to the droplet L in the ink jet printing apparatus of this embodiment, a droplet L in an additive

color can be accurately formed at a desired position. At this point, in the droplet L, a plurality of droplets do not express one additive color, but the droplet itself, that is, one dot expresses an additive color. Therefore, by the ink jet printing apparatus of this embodiment, a color image with high accuracy without distortion can be printed.

[0066] Furthermore, according to the ink jet printing apparatus of this embodiment, although the Taylor Cone 16 is formed, it stays within the inner diameter portion of the nozzle, the front end portion thereof becomes acute, and liquid can be quickly cut off when it is discharged.

Therefore, the distance between the dilute solution 8a and the flat electrode 3 can be shortened, and driving is carried out even by a comparatively small voltage. This effect eliminates the possibility of discharge between the dilute solution 8a and the flat electrode 3, and improves the reliability of the ink jet printing apparatus. Furthermore, by shortening the distance between the nozzle front end and the flat electrode 3, downsizing of the ink jet printing apparatus also becomes possible.

[0067] Furthermore, by the ink jet printing apparatus of this embodiment, in addition to the above-described effect, on-demand printing is also possible. Therefore, the ink jet printing apparatus of this embodiment is extremely effective as a micro printing apparatus of anticounterfeit printing technology.

[0068] In the above-described embodiment, the same voltage as the pulse voltage applied between the dilute solution and the flat electrode 3

is applied between the electrode 20 and the flat electrode when forming the droplet, however, it is preferable that a voltage greater than the pulse voltage applied between the dilute solution and the flat electrode 3 is applied between the electrode 20 and the flat electrode 3. In this case, the electrostatic inductive charge 21 appearing at the front end of the electrode 20 biases the charge distribution of the electrostatic inductive charge 161 on the dilute solution surface so that the distribution becomes highest at the nozzle center portion, so that a great electrostatic force acts on the portion with the high charge density, that is, between the center portion of the dilute solution surface and the flat electrode 3. Therefore, the position where the droplet is formed can be further stabilized, and a color image with high accuracy without distortion can be printed.

[0069] In the above-described embodiment, the electrode 20 is provided for only the dilution nozzle 8, however, it is preferable that the electrode 20 is also provided for the ink nozzles 9a through 9d.

In this case, when the primary color inks are discharged, smaller unit quantities of the primary color inks made of liquids that can be quickly cut off can be injected into the droplet L.

[0070] The invention is not limited to the above-described first and second embodiments. For example, the first and second embodiments relate to ink jet printing apparatuses and use primary color inks or dilute solution as raw material liquids, however, as raw material liquids, the

mixed liquid droplet forming apparatus of this embodiment can also use a conductive liquid (for example, a silver paste or mercury) instead of the primary color inks and dilute solution. In this case, liquids independently discharged from the respective nozzles can be accurately mixed on a droplet forming object. Furthermore, this conductive liquid droplet forming apparatus functions as an apparatus for forming fine two-dimensional electrical circuits (electrical wires, resistors, capacitors, reactance, and so on). As the raw material liquid, an insulating liquid such as silicon oil or machine oil, etc., may be used instead of the conductive liquid.

[0071]

[Effect of the Invention]

As described above, according to the mixed liquid droplet forming method and forming apparatus of the invention, liquids independently discharged from the nozzles can be accurately mixed on a droplet forming object.

[0072] Furthermore, according to the ink jet printing method and apparatus of the invention, primary color inks or dilute solution independently discharged from the nozzles can be accurately mixed on a printing object and a droplet in an intended additive color can be accurately formed.

[0073] Furthermore, according to the ink jet printing electrode-attached nozzle of the invention, when it is an ink jet printing apparatus including a flat electrode, a printing object is disposed between the

nozzle and the flat electrode, and a voltage is applied between an ink or dilute solution housed in the nozzle and the electrode and a potential higher than that of the ink or the dilute solution is supplied to the electrode, whereby the electrical line of force further concentrates immediately under the electrode-attached nozzle, so that it becomes possible to accurately dispose the ink or dilute solution at a desired position on the printing object. Therefore, when the ink or dilute solution is discharged to the printing object thereafter, it can be accurately mixed with the droplet on the printing object.

[Brief Description of the Drawings]

[Fig. 1]

A schematic sectional view showing a main part of an embodiment of the ink jet printing apparatus of the invention;

[FIG 2]

A bottom view of a nozzle head;

[FIG 3]

A partial sectional view of a dilution nozzle;

[FIG 4]

(a) is a timing chart of pulse voltage in nozzle, (b) to (f) are diagrams each showing a series of processes for forming a droplet in an additive color.

[FIG 5]

A flowchart showing processes for accurately realizing an intended additive color;

[FIG 6]

A schematic sectional view showing a main part of another embodiment of the ink jet printing apparatus of the invention;

[FIG 7]

- 5 A schematic sectional view showing an example of a conventional ink jet printing apparatus.

[Explanation of Reference Numerals]

- 1...ink jet printing apparatus、3...flat electrode、4...recording sheet (printed material, droplet forming object)、L...droplet 、8...dilution nozzle 、 9a~9d...ink nozzle 、 10...voltage applying unit 、 13...(illuminating light source 、 14...chroma measuring unit 、 15...control unit 、 20...electrode, 21...electrostatic inductive charge appearing at the front end of the electrode 20, 161...electrostatic inductive charge on the surface of the dilute solution.

15

[Document Name] ABSTRACT

[Problem]

5 A mixed liquid droplet forming method and apparatus, an ink jet printing method and apparatus, and an ink jet printing electrode-attached nozzle are provided, by which liquids to be discharged independently from each nozzle can be accurately mixed on a droplet forming object.

[Means of Solution]

10 The invention provides an ink jet printing method for printing a color image on a printing object by using a plurality of inks, wherein ink nozzles 9a through 9d which house the plurality of inks, respectively, and a dilution nozzle 8 which houses a dilute solution that can dilute the inks are used, the ink is discharged from the ink nozzle 9a by an electrostatic sucking force to form a droplet L on a printing object 4,
15 and then the ink is discharged from the ink nozzle 9b by an electrostatic sucking force and the inks are mixed within the droplet L to form a droplet in an arbitrary additive color. In this case, primary color inks can be accurately mixed within the droplet L.

[Selected Drawing] Fig. 1





Fig.2

Fig.3







Fig. 4




(b)




(c)




(d)



(e)



(f)



5/7


Fig.5


Fig.6

Fig. 7

